




Heyco® Thick Panel Vent Plugs

Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)
Mounting Hole Diameter Range: .500" (12,7 mm) to 2.000" (50,8 mm)

MOUNTING HOLE DIAMETER		PART NO.		DESCRIPTION	No. of Vent Holes	PART DIMENSIONS		B	
in.	mm.	Black	White			Head Diameter in.	mm.	Overall in.	Height mm.
.500	12,7	3010	3011	VPT 500	4	.578	14,7	.562	14,3
.625	15,9	3013	3014	VPT 625	5	.734	18,7		
.750	19,1	2426	2427	VPT 750	8	.906	23,0		
.875	22,2	3152	3153	VPT 875	9	1.015	25,8		
1.000	25,4	3154	3155	VPT 1000	9	1.203	30,6		
1.093 - 1.125	27,8 - 28,6	3032	3033	VPT 1093	9	1.218	30,9		
1.187	30,1	3160	3161	VPT 1187	10	1.312	33,3		
1.250	31,7	3034	3035	VPT 1250	10	1.375	34,9		
1.375	34,9	3036	3037	VPT 1375	11	1.500	38,1		
1.500	38,1	3156	3157	VPT 1500	13	1.671	42,4		
1.750	44,5	3038	3039	VPT 1750	13	1.906	48,4		
2.000	50,8	3158	3159	VPT 2000	19	2.140	54,4	.579	14,7

Standard color black. Consult Heyco for other colors.

- For use in panels thicker than .125" (3,2 mm).
- Permit the passage of air for ventilation and heat dissipation.
- Convex, matte finish head tapers to a thin edge.
- Locking fingers snap into holes with fingertip pressure for quick and easy installation.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Withstand a push back force of 35 pounds (47 Nm).
- Approximate Head Thickness: .062" (1,6 mm). Thickness may vary.
- Heyco Louvered Plugs available, see page 12.



HEYClean™ Filter Insert Vent Plugs

Mounting Hole Diameter Range: .875" (22,2 mm) to 3.000" (76,2 mm)

MOUNTING HOLE DIAMETER		PART NO.		DESCRIPTION	No. of Vent Holes	PART DIMENSIONS		B			
in.	mm.	Black				Head Diameter in.	mm.	Overall in.	Height mm.		
Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)											
.875	22,2	4919		FIVP 875	9	1.015	25,8	.453	11,5		
1.000	25,4	4921		FIVP 1000	9	1.203	30,6				
1.093 - 1.125	27,8 - 28,6	4923		FIVP 1093	9	1.218	30,9				
1.375	34,9	4931		FIVP 1375	11	1.500	38,1				
1.500	38,1	4933		FIVP 1500	13	1.671	42,4				
2.000	50,8	4937		FIVP 2000	19	2.140	54,4				
Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)											
2.500	63,5	4939		FIVP 2.5	19	2.718	69,0			.750	19,1
3.000	76,2	4941		FIVP 3.0	26	3.150	80,0			.740	18,8

Standard color black. Consult Heyco for other colors.



- Filter inserts permit the passage of air for ventilation but limit liquid as well as dust and pest infiltration.
- Polyurethane foam filter will filter particle sizes 30 micron and larger.

Material	Nylon 6/6
Certifications (VPT only)	Recognized under the Component Program of Underwriters' Laboratories, File E51579 Certified by Canadian Standards Association, File 8919
Flammability Rating	94V-2
Material Temperature Index	257°F (125°C)–Maximum temperature on part not to exceed 221°F (105°C)

Quick Specs