



RoHS



## FEATURES

- Universal 85 - 305VAC or 120 - 431VDC input voltage
- Accepts AC or DC input (dual-use of same terminal)
- Operating ambient temperature range: -30℃ to +70℃
- Low standby power consumption, high efficiency
- High I/O isolation test voltage up to 4000VAC
- Low ripple & noise
- Output short circuit, over-current, over-voltage, over-temperature protection
- Safety according to UL/EN/IEC62368, EN60335, GB4943, EN61558
- Over-voltage class III (designed to meet EN61558)
- Operating altitude up to 5000m

LM150-23Bxx series is one of Mornsun's enclosed AC-DC switching power supply. It features universal AC input and at the same time accepts DC input voltage, cost-effective, low no load power consumption, high efficiency, high reliability and double or reinforced insulation. These converters offer excellent EMC performance and meet IEC/EN61000-4, CISPR32/EN55032, UL/EN/IEC62368, EN60335, GB4943 standards and they are widely used in areas of industrial, LED, street light control, electricity, security, telecommunications, smart home etc.

## Selection Guide

Certification	Part No.*	Output Power(W)	Nominal Output Voltage and Current (Vo/Io)	Output Voltage Adjustable Range(V)	Efficiency at 230VAC (%) Typ.	Max. Capacitive Load (μF)
UL, CE, CB (Pass) CCC (Pending)	LM150-23B12	150	12V/12.5A	10.2-13.8	86	10000
	LM150-23B15	150	15V/10A	13.5 -18	87	6000
	LM150-23B24	156	24V/6.5A	21.6 - 28.8	88	2400
	LM150-23B36	154.8	36V/4.3A	32.4 - 39.6	88	1200
	LM150-23B48	158.4	48V/3.3A	43.2 -52.8	89	600

Note: \*Use suffix "C" for terminal with protective cover and suffix "Q" for conformal coating.

\*\*Only LM150-23B12/15/24's safety according to EN60335

## Input Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Input voltage Range	AC input		85	--	305	VAC
	DC input		120	--	431	VDC
Input Voltage Frequency			47	--	63	Hz
Input Current	115VAC		--	--	4	A
	230VAC		--	--	2	
Inrush Current	115VAC	Cold start	--	30	--	
	230VAC		--	60	--	
Leakage Current	277VAC		<0.75mA			
Hot Plug			Unavailable			

## Output Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Output Voltage Accuracy	Full load range		--	±1	--	%
Line Regulation	Rated load		--	±0.5	--	
Load Regulation	0% - 100% load		--	±0.5	--	
Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	12V/15V	--	--	150	mV





# AC/DC 150W Enclosed Switching Power Supply

## LM150-23Bxx, LM150-23Bxx-C, LM150-23Bxx-Q series

**MORNSUN®**

		24V/36V/48V	--	--	200	
Temperature Coefficient			--	±0.03	--	%/°C
Minimum Load			0	--	--	%
Stand-by Power Consumption	Room temperature, 230VAC		--	--	0.5	W
Hold-up Time	115VAC		8	--	--	ms
	230VAC		40	--	--	
Short Circuit Protection	Recovery time <5s after the short circuit disappear.		Hiccup, continuous, self-recovery			
Over-current Protection			110%-150% Io, self-recovery			
Over-voltage Protection	12V		≤16.2VDC (Output voltage turn off/hiccup)			
	15V		≤21.75VDC (Output voltage turn off/hiccup)			
	24V		≤33.6VDC (Output voltage turn off/hiccup)			
	36V		≤48.6VDC (Output voltage turn off/hiccup)			
	48V		≤60VDC (Output voltage turn off/hiccup)			
Over-temperature Protection	Output voltage turn off, self-recovery					
Note: *The "Tip and barrel method" is used for ripple and noise test, output parallel 47uF electrolytic capacitor and 0.1uF ceramic capacitor, please refer to Enclosed Switching Power Supply Application Notes for specific information.						

## General Specifications

Item		Operating Conditions		Min.	Typ.	Max.	Unit
Isolation	Input - 	Electric strength test for 1min., leakage current <10mA		2000	--	--	VAC
	Input-output			4000	--	--	
	Output - 			1250	--	--	
Insulation Resistance	Input - 	At 500VDC		50	--	--	MΩ
	Input - output			50	--	--	
	Output - 			50	--	--	
Operating Temperature				-30	--	+70	℃
Storage Temperature				-40	--	+85	
Storage Humidity		Non-condensing		10	--	95	%RH
Operating Humidity		Non-condensing		20	--	90	
Switching Frequency				--	65	--	kHz
Power Derating	Operating temperature derating	<100VAC Input	-30℃ to -25℃	5	--	--	% /℃
		12V	+45℃ to +70℃	2	--	--	
		15V/24V/36V/48V	+50℃ to +70℃	2.5	--	--	
	Input voltage derating	85VAC-100VAC		1.33	--	--	% /VAC
		277VAC-305VAC		0.714	--	--	
Safety Standard				Meet UL/EN/IEC62368/EN60335 / GB4943/EN61558			
Safety Certification				UL/EN/IEC62368 (Pass) GB4943, EN61558, EN60335 (pending)			
Safety Class				CLASS I			
MTBF		MIL-HDBK-217F@25℃		>300,000 h			
Note: It is recommended to use part number with "Q" for applications in harsh environments such as salt spray, chemical, humidity.							

## Mechanical Specifications

Case Material	Metal (AL1100, SGCC)		
Dimensions	159.00 x 97.00 x 30.00 mm		
Weight	12V/15V	430g (Typ.)	
	24V/36V/48V	410 (Typ.)	
Cooling Method	Free air convection		

**MORNSUN®**

MORNSUN Guangzhou Science & Technology Co., Ltd.

2020.04.23 -A/0



Page 2 of 5

MORNSUN Guangzhou Science & Technology Co., Ltd. reserves the copyright and right of final interpretation

## Electromagnetic Compatibility (EMC)

Emissions	CE	CISPR32/EN55032	CLASS B	
	RE	CISPR32/EN55032	CLASS B	
	Harmonic current	IEC/EN61000-3-2	CLASS A ( $\leq 80\%$ Load)	
Immunity	ESD	IEC/EN 61000-4-2	Contact $\pm 6\text{KV}$ /Air $\pm 8\text{KV}$	Perf. Criteria A
	RS	IEC/EN 61000-4-3	10V/m	perf. Criteria A
	EFT	IEC/EN 61000-4-4	$\pm 4\text{KV}$	perf. Criteria A
	Surge	IEC/EN 61000-4-5	line to line $\pm 2\text{KV}$ /line to ground $\pm 4\text{KV}$	perf. Criteria A
	CS	IEC/EN61000-4-6	10 Vr.m.s	perf. Criteria A
	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11	0%, 70%	perf. Criteria B


## Product Characteristic Curve




Note: ① With an input voltage between 85 -100VAC/277-305VAC and a DC input between 120 -140VDC/391-431VDC the output power must be derated as per the temperature derating curves;

② This product is suitable for applications using natural air cooling; for applications in closed environment please consult Mornsun FAE.

Efficiency Vs Input Voltage (Full Load)




Efficiency Vs Output Load (Vin=230VAC)




Dimensions and Recommended Layout

LM150-23Bxx, LM150-23Bxx-Q Series



LM150-23Bxx-C Series



Note:

1. For additional information on Product Packaging please refer to [www.mornsun-power.com](http://www.mornsun-power.com). Packaging bag number: 58220111;
2. Unless otherwise specified, parameters in this datasheet were measured under the conditions of  $T_a=25^{\circ}\text{C}$ , humidity<75%RH with nominal input voltage and rated output load;
3. The room temperature derating of  $5^{\circ}\text{C}/1000\text{m}$  is needed for operating altitude greater than 2000m;
4. All index testing methods in this datasheet are based on our company corporate standards;
5. In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability;
6. We can provide product customization service, please contact our technicians directly for specific information;
7. Products are related to laws and regulations: see "Features" and "EMC";
8. The output case need to be connected to the earth (⏚) of system when the terminal equipment in operating;
9. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

## Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China

Tel: 86-20-38601850

Fax: 86-20-38601272

E-mail: [info@mornsun.cn](mailto:info@mornsun.cn)

[www.mornsun-power.com](http://www.mornsun-power.com)