

Print this Page




- Housing: Die-Cast Aluminum, Painted Black
- Blade: Thermoplastic UL 94V-0 P.B.T.
- Insulation Resistance: 100MΩ, 500VDC/min between bare wire and frame
- Dielectric Strength: 1500VAC for one minutue
- Operation Temperature: -20°C~70°C (Humidity 35%-85%RH)
- Storage Temperature: -40°C~85°C (Humidity 35%-85%RH)
- Motor Protection: Impedance Protected
- Weight: 515 g

Characteristic Curves:



Outline Drawing:



Specification:

Model Number	Bearing Availability	Rated Voltage (VAC)	Frequency (Hz)	Rated Current (mA)	Power (W)	Speed (RPM)	Air Flow (CFM)	Static Pressure (mm-H2O)	Noise (dBA)
FA1238B11T1-51	2Ball	115	50/60	80/70	7/6	1,900/1,700	61.0/56.0	2.3/1.8	34.0/33.0
FA1238B11T3-51			50/60	130/110	11/10	2,000/1,900	61.0/64.0	2.7/2.1	34.0/35.0
FA1238B11T5-51			50/60	140/130	11/11	2,500/2,500	83.0/81.0	5.2/2.2	43.0/42.0
FA1238B11T7-51			50/60	260/210	20/16	2,600/3,000	85.0/97.0	7.1/6.7	44.0/48.0

FA1238B22T1-51	or Sleeve	230	50/60	50/40	9/8	1,900/1,800	59.0/59.0	2.3/1.8	33.0/33.0
FA1238B22T3-51			50/60	70/60	12/10	1,900/2,000	61.0/64.0	2.7/2.1	34.0/35.0
FA1238B22T5-51			50/60	70/60	12/11	2,500/2,500	83.0/81.0	5.2/2.2	43.0/42.0
FA1238B22T7-51			50/60	130/100	20/16	2,600/3,000	85.0/97.0	7.1/6.7	44.0/48.0

- For Wire lead version, change "T" in the model number to "W".
- For Sleeve Bearing version, change"B"in the model number to "S".

Specifications are subject to change without notice

Accessories:

Fans are available with a wide range of accessories

Part Type	Wire Form Guard	Plastic Guard	Plastic Filter	Aluminum Filter	Power Cord
Part Number	FGW-120	FGP-120	FPF-120	FFA-120	Any Configuration