





## Heyco® Stainless Steel Cable Clamps

- For clamping cable or tubing securely into place, especially in **harsh environments**.
- Smooth "coined clamp" edges prevent damage to cable insulation.
- Constructed from corrosion resistant 304 stainless steel.
- Coated parts are constructed from 304 stainless steel and coated with polyolefin a thermoplastic co-polymer.
- Coating provides a durable non-toxic, odorless coating that has very good low temperature flexibility and excellent electrical properties. This coating also has **FDA food contact** approval.
- All parts require a .203" (5,2 mm) mounting hole suitable for a #10 screw.
- Not for use in a marine salt water environment. Contact Heyco for alternative materials.
- DFARS Compliant

| PART DIMENSION A |      | STANDARD     |              | COATED       |                                 |
|------------------|------|--------------|--------------|--------------|---------------------------------|
| in.              | mm.  | PART NO.     | DESCRIPTION  | PART NO.     | DESCRIPTION                     |
| .19              | 4,7  | <b>S3373</b> | CC H 3/16 SS | <b>S3323</b> | CC H 3/16 SS Coated <b>NEW!</b> |
| .25              | 6,3  | <b>S3374</b> | CC H 1/4 SS  | <b>S3324</b> | CC H 1/4 SS Coated              |
| .38              | 9,5  | <b>S3376</b> | CC H 3/8 SS  | <b>S3326</b> | CC H 3/8 SS Coated              |
| .50              | 12,7 | <b>S3378</b> | CC H 1/2 SS  | <b>S3328</b> | CC H 1/2 SS Coated              |
| .63              | 15,9 | <b>S3380</b> | CC H 5/8 SS  | <b>S3330</b> | CC H 5/8 SS Coated              |
| .75              | 19,1 | <b>S3382</b> | CC H 3/4 SS  | <b>S3332</b> | CC H 3/4 SS Coated              |
| .88              | 22,2 | <b>S3384</b> | CC H 7/8 SS  | <b>S3334</b> | CC H 7/8 SS Coated              |

Consult Heyco for additional sizes.



## Heyco® Steel Cushion Clamps



| MOUNTING HOLE DIA. | SCREW SIZE | PART DIMENSION A | PART NO. | PART NO.      | DESCRIPTION | MARKING | RUBBER THICKNESS |
|--------------------|------------|------------------|----------|---------------|-------------|---------|------------------|
| in.                | mm.        | in.              | mm.      | 304 Stainless |             |         | in. mm.          |

.650" (16,5 mm) Overall Width, .031" (0,8 mm) Steel Thickness


|      |     |     |      |      |              |              |              |       |     |     |
|------|-----|-----|------|------|--------------|--------------|--------------|-------|-----|-----|
| .265 | 6,7 | 1/4 | 0.19 | 4,7  | <b>12300</b> | <b>15730</b> | CCSC L 3/16  | 3/16  | .06 | 1,5 |
|      |     |     | 0.25 | 6,3  | <b>12301</b> | <b>15731</b> | CCSC L 1/4   | 1/4   |     |     |
|      |     |     | 0.31 | 7,9  | <b>12302</b> | <b>15732</b> | CCSC L 5/16  | 5/16  |     |     |
|      |     |     | 0.38 | 9,5  | <b>12303</b> | <b>15733</b> | CCSC L 3/8   | 3/8   |     |     |
|      |     |     | 0.44 | 11,1 | <b>12304</b> | <b>15734</b> | CCSC L 7/16  | 7/16  |     |     |
|      |     |     | 0.50 | 12,7 | <b>12305</b> | <b>15735</b> | CCSC L 1/2   | 1/2   |     |     |
|      |     |     | 0.56 | 14,3 | <b>12306</b> | <b>15736</b> | CCSC L 9/16  | 9/16  |     |     |
|      |     |     | 0.63 | 15,9 | <b>12307</b> | <b>15737</b> | CCSC L 5/8   | 5/8   |     |     |
|      |     |     | 0.69 | 17,4 | <b>12308</b> | <b>15738</b> | CCSC L 11/16 | 11/16 |     |     |
|      |     |     | 0.75 | 19,1 | <b>12309</b> | <b>15739</b> | CCSC L 3/4   | 3/4   |     |     |
|      |     |     | 0.88 | 22,2 | <b>12310</b> | <b>15740</b> | CCSC L 7/8   | 7/8   |     |     |
|      |     |     | 1.00 | 25,4 | <b>12311</b> | <b>15741</b> | CCSC L 1     | 1     |     |     |
|      |     |     | 1.13 | 28,6 | <b>12312</b> | <b>15742</b> | CCSC L 1-1/8 | 1-1/8 |     |     |
|      |     |     | 1.25 | 31,8 | <b>12313</b> | <b>15743</b> | CCSC L 1-1/4 | 1-1/4 |     |     |
|      |     |     | 1.50 | 38,1 | <b>12314</b> | <b>15744</b> | CCSC L 1-1/2 | 1-1/2 |     |     |
|      |     |     | 2.00 | 50,8 | <b>12315</b> | <b>15745</b> | CCSC L 2     | 2     |     |     |
|      |     |     | 2.50 | 63,5 | <b>12316</b> | <b>15746</b> | CCSC L 2-1/2 | 2-1/2 |     |     |
|      |     |     | 3.00 | 76,2 | <b>12317</b> | <b>15747</b> | CCSC L 3     | 3     |     |     |

.750" (19,1 mm) Overall Width, .047" (1,2 mm) Steel Thickness

|      |      |      |      |      |              |              |              |       |     |     |
|------|------|------|------|------|--------------|--------------|--------------|-------|-----|-----|
| .406 | 10,3 | 7/16 | 0.25 | 6,3  | <b>12331</b> | <b>15751</b> | CCSC H 1/4   | 1/4   | .06 | 1,5 |
|      |      |      | 0.31 | 7,9  | <b>12332</b> | <b>15752</b> | CCSC H 5/16  | 5/16  |     |     |
|      |      |      | 0.38 | 9,5  | <b>12333</b> | <b>15753</b> | CCSC H 3/8   | 3/8   |     |     |
|      |      |      | 0.44 | 11,1 | <b>12334</b> | <b>15754</b> | CCSC H 7/16  | 7/16  |     |     |
|      |      |      | 0.50 | 12,7 | <b>12335</b> | <b>15755</b> | CCSC H 1/2   | 1/2   |     |     |
|      |      |      | 0.63 | 15,9 | <b>12337</b> | <b>15757</b> | CCSC H 5/8   | 5/8   |     |     |
|      |      |      | 0.69 | 17,4 | <b>12338</b> | <b>15758</b> | CCSC H 11/16 | 11/16 |     |     |
|      |      |      | 0.88 | 22,2 | <b>12340</b> | <b>15760</b> | CCSC H 7/8   | 7/8   |     |     |
|      |      |      | 1.00 | 25,4 | <b>12341</b> | <b>15761</b> | CCSC H 1     | 1     |     |     |
|      |      |      | 1.25 | 31,8 | <b>12343</b> | <b>15763</b> | CCSC H 1-1/4 | 1-1/4 |     |     |
|      |      |      | 1.50 | 38,1 | <b>12344</b> | <b>15764</b> | CCSC H 1-1/2 | 1-1/2 |     |     |
|      |      |      | 2.00 | 50,8 | <b>12345</b> | <b>15765</b> | CCSC H 2     | 2     |     |     |
|      |      |      | 2.50 | 63,5 | <b>12346</b> | <b>15766</b> | CCSC H 2-1/2 | 2-2/2 |     |     |
|      |      |      | 3.00 | 76,2 | <b>12347</b> | <b>15767</b> | CCSC H 3     | 3     |     |     |



- Light to heavy duty steel clamp.
- E.P.D.M. cushion for electrical insulation and vibration absorption.
- Steel clamps are zinc electroplated for corrosion resistance.
- 304 Stainless Steel clamps for superior corrosion resistance for harsh environments.
- Color - Silver with durable black cushion.



Material **CC H** 304 Stainless Steel  
Temperature Range 0°C (32°F) to 60°C (140°F)

**CCSC** Zinc Plated Steel and 304 Stainless Steel with a UV resistant EPDM Sleeve  
-40°C (-40°F) to 100°C (212°F)