

Specification Sheet

Part Number: 151-04681

Large footprint and acrylic adhesive deliver excellent, long-lasting adhesion.

Part architecture and large size eliminate need for multiple standard adhesive mounts, allowing for part consolidation and savings.

Retention arm enables installers to stage cable installation before permanently fastening.

Unique EZ Feed cable tie slot eliminates common obstructions for faster completion.

Integrated holes for mechanical fastening if desired.



Acrylic Adhesive Anchor Mount, 2.4 x 2.4", Use With T18-T120 Cable Ties or GT.375 Grip Tie, PA66HS, White, 50/bag

Article Number	151-04681
----------------	-----------

Type	AMB6AHB
------	---------

Color	White (WH)
-------	------------

Quantity Per	bag
--------------	-----

Product Description	The HellermannTyton Anchor Mount is specially designed for areas that see excessive movement, stress or tension, particularly around hinges or corners. It provides heavy duty strength and adhesion with its extra-large surface area and high-bond acrylic adhesive. The radius guide helps hold and guide bundles up and around hinges, corners, or other obstructions. The mount features a retention arm to help hold wires in place during the planning phases of cable installations, allowing for rework if needed.
Short Description	Acrylic Adhesive Anchor Mount, 2.4 x 2.4", Use With T18-T120 Cable Ties or GT.375 Grip Tie, PA66HS, White, 50/bag
Global Part Name	AMB6AHB-PA66HS-WH
Length L (Imperial)	2.4
Length L (Metric)	62.0
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	2.4
Width W (Metric)	62.0
Height H (Imperial)	1.1
Height H (Metric)	27.2
Mounting Hole Diameter D (Imperial)	0.18 "
Mounting Hole Diameter D (Metric)	4.5 mm

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Adhesive	High Bond Acrylic
Flammability	UL 94 V-2 (excluding adhesive)
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Adhesive Operating Temperature	-31°F to +158°F (-35 °C to +70 °C)
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)