

“Stay Connected” with



Solar Power Components

a PennEngineering® Company





- The NEW Heyco SunRunner Short Flange attaches to newer modules with smaller frames.
- Minimum flange depth requirement of only 10 mm and holds as tight as our popular SunRunner series.
- Heyco SunRunner Clips are designed to provide a better method for PV module wire management and may be used wherever single or multiple cable management is needed.
- Smooth clip edges prevent damage to cable insulation.
- Locking tabs securely fasten clips to module extrusions, or other panels.
- Generous lead-in for installation without tools.
- Neatly dresses cables on PV panel frames or along mounting channels.
- Constructed from corrosion-resistant 304 stainless steel; not for use in a marine salt water environment.


HEYClip™ SunRunner® Short Flange

Double-Compression, Straight-thru Design

| PANEL THICKNESS CLAMPING RANGE | | WIRE DIA. RANGE | | PART NO. 304 Stainless | DESCRIPTION | FOOTPRINT A x B | | OVERALL HEIGHT C | |
|---|----------------------|----------------------|----------------------|--|-------------|-------------------------------------|--------------|---------------------|-----------|
| Minimum in. mm. | Maximum in. mm. | Minimum in. mm. | Maximum in. mm. | | | in. | mm. | in. | mm. |
| SunRunner Clip – for panels up to .093" (2,36 mm) thick | | | | | | | | | |
| .025 | 0,64 | .093 | 2,36 | .20" (5,1 mm) - .30" (7,6 mm) each cable | S6570 | SunRunner® Short Flange 100 Pack | .97 x .50 | 24,6 x 12,7 | .39 9,9 |
| | | | | | S6571 | SunRunner® Short Flange Bulk | | | |



CHASSIS THICKNESS
.025" (0,64 mm) - .093" (2,36 mm)



MINIMUM PANEL FLANGE DEPTH
0.40" (10,0 mm)






- The NEW Heyco SunRunner 90° Short Flange attaches to newer modules with smaller frames.
- Minimum flange depth requirement of only 10 mm and holds as tight as our popular SunRunner series.
- The NEW 90° orientation provides cable routing perpendicular to panel edge
- Locking tabs securely fasten clips to module extrusions, or other panels.
- Constructed from corrosion-resistant 304 stainless steel; not for use in a marine salt water environment.
- UL Pending


HEYClip™ SunRunner® Short Flange 90° Cable Clips

Double-Compression, Right Angle Design

| PANEL THICKNESS CLAMPING RANGE | | WIRE DIA. RANGE | | PART NO. 304 Stainless | DESCRIPTION | FOOTPRINT A x B | | OVERALL HEIGHT C | |
|--|----------------------|----------------------|----------------------|--|-------------|---|--------------|---------------------|-----------|
| Minimum in. mm. | Maximum in. mm. | Minimum in. mm. | Maximum in. mm. | | | in. | mm. | in. | mm. |
| Double Wire 90° Clip – for panels up to .100" (2,5 mm) thick | | | | | | | | | |
| .032 | 0,8 | .100 | 2,5 | .20" (5,1 mm) - .33" (8,4 mm) each cable | S6575 | SunRunner® 90° Short Flange 100 Pack | .99 x .50 | 25,1 x 12,7 | .39 9,9 |
| | | | | | S6576 | SunRunner® 90° Short Flange Bulk | | | |



CHASSIS THICKNESS
.032" (0,8 mm) TO
.100" (2,5 mm)



HOLDS TWO (2) CABLES OF EQUAL DIAMETER
RANGING IN Ø .20" (Ø 5,1 mm) TO Ø .33" (Ø 8,4 mm)

Quick Specs

| | |
|-------------------|---|
| Material | .025" thick 304 Stainless Steel |
| Certifications | cULus Certified by UL for Compliance with both Canadian and US Requirements under File E54523 |
| Temperature Range | -40°F (40°C) to 572°F (300°C) |