

- Housing: Die-Cast Aluminum, Painted Black
- Blade: Thermoplastic UL 94V-0 P.B.T.
- Insulation Resistance: 100MΩ, 500VDC/min between bare wire and frame
- Dielectric Strength: 1500VAC for one minutue
- Operation Temperature: -20°C~70°C (Humidity 35%-85%RH)
- Storage Temperature: -40°C~85°C (Humidity 35%-85%RH)
- Motor Protection: Impedance Protected
- Weight: 346 g

CE

Characteristic Curves:



Outline Drawing:



Specification:

Model Number	Bearing Availability	Rated Voltage (VAC)	Frequency (Hz)	Rated Current (mA)	Power (W)	Speed (RPM)	Air Flow (CFM)	Static Pressure (mm-H2O)	Noise (dBA)
FA1225B11T7-51※	2Ball or Sleeve	115	50/60	150/120	13/10	2,600/3,100	61.0/72.0	5.6/6.3	42.0/45.0
FA1225B22T7-51※		230	50/60	70/60	13/10	2,600/3,000	61.0/72.0	5.6/6.3	42.0/45.0

- For Wire lead version, change "T" in the model number to "W".
- If model with "※", the safety is pending.
- For Sleeve Bearing version, change"B"in the model number to "S".

Specifications are subject to change without notice

Accessories:

Fans are available with a wide range of accessories

Part Type	Wire Form Guard	Plastic Guard	Plastic Filter	Aluminum Filter	Power Cord
Part Number	FGW-120	FGP-120	FPF-120	FFA-120	Any Configuration