

Press Release

Lucerne, 04.09.2012
M470



5123

Compact filtered inlet boasts maximum attenuation

SCHURTER's latest 5123 series filtered inlet adds filter performance to the already successful standard version 5120 series. The higher attenuation in the same compact dimensions is designed to meet the continually increasing demands for interference suppression of IT, medical, test & measurement and industrial equipment.



The new 5123 series filter combines an IEC power inlet and a line filter, designed for nominal currents up to 15A. The combination power entry unit integrates the EMC filter directly at the line input, providing an optimal effect on electromagnetic compatibility. The broad metal flange features a large amount of contact area, which further optimizes filtering and shielding effects. The filter's increased inductance achieves a 6 dB improvement in asymmetric attenuation, compared to 5120 series and other like products on the market, corresponding to a doubling of its attenuation characteristics. Thus, the high filter performance makes the 5123 series well suited for applications such as switched-mode power supplies, where the utmost interference suppression is required.

The 5123 series is available for snap-in, screw-in or studded assembly. Screw-in assembly from the back side is particularly attractive for a plastic chassis with interior metal layers. Wiring is done with quick-connect, solder, stranded-wire or pc-board terminals. The PC version features snap-in feet for secure pc-board mounting. The stranded-wire version enables customer specific fitting for further cost-effective wiring.

The 5120 and enhanced 5123 are designed for operating current levels up to 10A at 250 VAC according to IEC and 15A at 125/250 VAC according to UL. They are ENEC and cURus approved. The two series are offered in standard and medical versions suitable for use in IT applications according to IEC 60950, and medical applications according to IEC 60601-1.

Features:

- Very high attenuation
- Nominal current: up to 10A at 250 VAC (ENEC/UL/CSA) and 15A at 125/250 VAC (UL/CSA)
- Screw-in or studded assembly / snap-in assembly
- Connections: quick-connect, solder, stranded-wire or pc-board terminals
- Filters available in standard and medical versions
- Optionally available with the V-Lock cable locking system

Internet:

[5123 Microsite](#) [1]

Contact:

Should you have any questions regarding these or other SCHURTER products, please contact:

Division Components
SCHURTER Group

SCHURTER AG
Product Marketing
Werkhofstrasse 8-12
PO Box
6002 Lucerne
Switzerland
T +41 41 369 31 11

contact@schurter.ch
schurter.com

[1]: <http://5123.schurter.com>