PRO LINE PROPERTY OF THE PROP







47002BCSBP



6-Pack Contains All Six Products 80606SBP



88-Piece Rack

80607SBP

VC-3 Threadmate Non-Traditional Threadlocker

- · Adjustable, Removable, Reusable
- Prevents fasteners from loosening due to shock and vibration.
- Locks and seals threaded fasteners of virtually any size.
- Works with metal, wood, plastic, and more.
- Temp Range: -65°F to +165°F

NET 0.17 FL 0Z (5 mL)

Threadlocker Gel Permanent Strength (Red)

30114BCSBP

- Permanently locks fasteners up to 1" in diameter.
- No drip. No waste.
- Torque Break: 200 in/lbs
- Torque Prevail: 100 in/lbs
- Temp Range: -65°F to 300°F

NET 0.26 FL 0Z (8 mL)



Threadlocker Gel Medium Strength (Blue)

90729BCSBP

- Removable, for 1/4" to 3/4" diameter fasteners.
- · No drip. No waste.
- Torque Break: 120 in/lbs
- Torque Prevail: 45 in/lbs
- . Temp Range: -65°F to 300°F



NET 0.26 FL 0Z (8 mL)

Instant SuperGlue Multi-Purpose

- Quick Fixturing, Fast Setting.
- High Strength.
- Pinpoint Precision Tip.
- · Surface Insensitive.
- For Metal, Plastic, Rubber, Ceramic, Cork, Paper, Wood, Leather, Fabrics, Vinyl, & more.
- Sporting, Household, Automotive, Marine, Crafts.

NET 0.5 FL 0Z (15 mL)

DriveGripAnti Cam-Out Fluid

- Assembly aid to help prevent fastener slippage.
- Minimizes drilled-out screws, easy-outs, and retapping.
- Increases grip between fastener head and tool by up to 700%.
- Virtually eliminates tool wear and deforming of fasteners.

NET 0.5 FL 0Z (15 mL)

Anti-Seize Compound Nickel-Graphite

- Formulated to reduce excessive wear on threads, gears, chains, cables, sprockets, and rollers.
- Prevents excessive wear, seizing, galling, and cold welding.
- Excellent resistance to harsh chemicals.
- Works in temperatures from -300°F to 2,000°F.

NET 0.26 FL 0Z (8 mL)



Distributed in Canada by (



CENTRALsales@ Aurora, ON WESTsales@ EASTsales@ Dorval, QC USAsales@

Town

irwin-ind.com 800-263-3562