


# ANTI-SEIZE 917N PRE-APPLIED

Lubricant



## DESCRIPTION:

Antiseize 917N is a pre-applied lubricant meant to prevent galling of metals at high temperatures. This water-based material is applied to threaded fasteners and subsequently dried to a non-tacky coating. This material effectively lubricates threaded assemblies, permitting easy disassembly in temperatures of up to 1,200°F (650°C). This material was developed to meet specification GM6108M.



## SPECIFICATIONS:

As Applied Properties	
Color	Metallic Gray
Brookfield Viscosity (ASTM D1084-97, B)	1,000 - 1,300 cp (spindle #2/20 rpm)
#4 Zahn Viscosity (ASTM D1084-97, D)	22 - 26 seconds
VOC Content (ASTM D2369-98)	< 0.5 lb./gal.
Percent Solids by Weight (ASTM D2369-98)	35 - 43%
Specific Gravity (ASTM D2369-98)	1.41
Temperature	Up to 1,200°F ( 650°C)

Anti-Seize 917N Pre-Applied is a product of ND Industries, Inc., U.S.A.



Distributed in Canada by \_\_\_\_\_

**WESTsales@**  
115-1440 Aviation Park NE  
Calgary, AB  
T2E 7E2  
403-291-3516



**CENTRALsales@**  
2-205 Industrial Pky N  
Aurora, ON  
L4G 4C4  
905-889-9100

**EASTsales@**  
492 Avenue Lépine  
Dorval, QC  
H9P 2V6  
514-556-3064

**USAsales@**  
2775 Broadway Ave  
Buffalo, NY  
14227  
905-889-9100

800-560-9813

irwin-ind.com

800-263-3562